



TECHNOLOGY 238 XT CE/MPGE 230V ACX+CASE



NEW

Overview

TECHNOLOGY 238 XT CE/MPGE 230V ACX+CASE

cod. 816252

MMA and TIG inverter, electrode welding machine in direct current (DC) with scratch striking.

Use with a wide range of electrodes: rutile, basic, stainless steel, cast iron, cellulosic, etc.

Recommended for motogenerators, this model grants high performance despite power supply instability, thanks to the MPGE multiprotections: control device of the wave form, filter against input peaks, stabilization of oscillations. Robust and impact resistant.

Features:

- compact and light
- Ø 50mm quick connector (socket)
- high welding current stability in spite of mains voltage fluctuations
- regulation of arc force and hot start according to the type of electrode in use
- anti-stick device
- thermostatic, overvoltage, undervoltage, overcurrent protections.

Complete with MMA welding accessories and aluminium carry case.



1 PH 230V



CE MARKING



EAC CERTIFICATION

Technical data



CODE 816252



MAX NO LOAD VOLTAGE 80 V



POWER FACTOR (cosphi) 0,7



SINGLE PHASE MAINS VOLTAGE 230 V



MAX ABSORBED CURRENT 39 A



D. USABLE ELECTRODES IN DC 1,6 - 4 mm



MAINS FREQUENCY 50 / 60 Hz



ABSORBED CURRENT AT 60% - MAX 20 A



CURRENT RANGE 5 - 200 A



MAX ABSORBED POWER 6,3 kW



PROTECTION DEGREE IP23



MAX CURRENT DC (EN 60974-1) 200 @ 35 % A



TECHNOLOGY 238 XT CE/MPGE 230V ACX+CASE

ABSORBED POWER AT 60% 3 kW	DIMENSIONS 37,5 x 50 x 22 cm	MOTORGENERATOR MINIMUM POWER 10 kW
WEIGHT 10,55 kg	DC CURRENT 140 A	EFFICIENCY 87 V

Included Accessories

CABLE - 124887



TOLEDO 300 WORK CLAMP - 712231

CABLE TW05V-A 1X025 L=02.00M DINSE - 125033



DALLAS 300 ELECTRODE HOLDER 300A - 712260