



TECHNOMIG 260 DUAL SYNERGIC



Overview

TECHNOMIG 260 DUAL SYNERGIC

cod. 816056

Microprocessor controlled MIG-MAG/FLUX/BRAZING/MMA/ TIG DC-Lift inverter multiprocess welding machine. Technomig Dual Synergic is confirmed as the perfect solution for a wide range of applications, from maintenance to installation and interventions in body shops, because of its flexibility and the different materials it can weld (steel, stainless steel, aluminium) or braze weld (galvanized sheet).

The quick SYNERGIC regulation of the welding parameters, thanks to the ONE TOUCH LCD SYNERGY technology, makes this product easy to use. The intelligent and automatic control of the arc, moment by moment, maintains high welding performance in all working conditions, with different materials and/or gases.

The operator can also intervene manually along the arc length: this adjustment means the weld seam can be modified according to the welder's style.

The ONE TOUCH LCD graphic display allows for a better reading of all welding parameters.

Lightweight and very compact, Technomig can be moved around easily in all intervention areas, both indoors and outdoors.

Features:

- polarity reversal for NO GAS/Flux, MIG-MAG/BRAZING welding;
- 29 synergy curves available;
- visualization on LCD display of voltage, current, welding speed;
- regulation of: wire speed up slope, electronic reactance, burn-back time, post gas;
- choice of 2/4 times, spot operation;
- thermostatic, overvoltage, undervoltage, overcurrent, motorgenerator (+/- 15%) protections.

Complete with MIG-MAG torch, work clamp and cable.



MMA TIG DC LIFT



1 PH 230V



CE MARKING



MIG-MAG FLUX



COIL 15 kg



EAC CERTIFICATION

Technical data



CODE 816056



MAX ABSORBED CURRENT 39 A



D. USABLE ELECTRODES IN DC 1,6 - 4 mm



TECHNOMIG 260 DUAL SYNERGIC

SINGLE PHASE MAINS VOLTAGE 230 V	ABSORBED CURRENT AT 60% - MAX 22 A	STEEL WELDING WIRE DIAMETER 0,6 - 1,2 mm
MAINS FREQUENCY 50 / 60 Hz	MAX ABSORBED POWER 6,3 kW	INOX WELDING WIRE DIAMETER 0,8 - 1 mm
CURRENT RANGE 20 - 250 A	ABSORBED POWER AT 60% 3,3 kW	ALUMINIUM WELDING WIRE DIAM. 0,8 - 1 mm
MAX CURRENT DC (EN 60974-1) 220 @ 20% A	EFFICIENCY 87 V	FLUX CORED WELDING WIRE DIAM. 0,8 - 1,2 mm
DC CURRENT 130 A	POWER FACTOR (cosphi) 0,7	BRAZING WIRE DIAM. 0,8 - 1 mm
MAX NO LOAD VOLTAGE 60 V		

Included Accessories

CABLE - 124887	MT25 MIG TORCH 3M - 742183
TOLEDO 300 WORK CLAMP - 712231	FEED ROLL 2R 0,6FE-0,8FE "F" - 742575